



Pure water system PROTEUS



The “all-in-one” system PROTEUS systems fulfils highest standards for a reliable supply of pure water and maximum operational safety. Everything in one space-saving cabinet.

The ready-for-connection pure water system PROTEUS has been developed to economically produce high quality pure water and pump it, as required, to complete laboratory storeys and doctor’s offices, where space is scarce. Pre-treatment, reverse osmosis, optional EDI purification steps, a pure water tank and a booster pump are compactly combined and mounted in a compact cabinet. The modern touch interface controls all operating and performance parameters. The pure water that the systems produce complies with appropriate standards such as ASTM and DIN EN 285 & 15883.



Features

- ✓ Large and intuitive touchscreen
- ✓ Leak water detector
- ✓ Reverse-osmosis module for desalination and removal of up to 99% organic and inorganic impurities
- ✓ Pressure reducer
- ✓ Data capture via USB
- ✓ Dry-run protection
- ✓ Internal 80l tank with complete recirculation ensures the highest microbial purity
- ✓ Booster pump with convenient constant pressure control for low-noise delivery of pure water to the end user
- ✓ **Optional** EDI module as residual desalination for consistently highest pure water quality
- ✓ **Optional** external dispenser
 - ◆ detachable and ergonomically shaped
 - ◆ rotatable and vertically adjustable
 - ◆ accurate, adjustable volume dispensing

System configuration

- Wide-range power supply 80-264V / 50-60Hz
- Compact production unit fits easily into various free spaces in the lab
- Integrated pressure reducer for different inlet pressures
- Flow meter for an accurate measuring of the production rate
- Pressure sensor for monitoring of the working pressure and as a dry-running protection
- Low-noise and durable RO pressure pump
- RO membrane removes up to 99% of all impurities in the feed water
- Flush valve for the effective cleaning of all wetted parts as well as an adjustable quality flush during stand-by
- Internal pure water tank with sloped bottom and pure water outlet

User interface

- Large and intuitive touchscreen
- Individual adjustment for displaying the conductivity (MΩcm or μS/cm)
- Multilevel conductivity and temperature monitoring for pure and ultrapure water, temperature compensated with stepless limit adjustments
- High-precision measuring with integrated reference resistors as well as deactivatable temperature compensation acc. to USP
- Leakage monitor with error message and automatic shut-off of the feed water supply
- Continuous surveillance of all relevant parameters and values incl. early reminders when a change of consumables is pending



Pure water tank 80L

Storage tank for the storage of pure water fed in from the reverse osmosis. Made of black PE. Closed, square and opaque construction, with a 200 mm inspection opening for cleaning. The tank is supplied completely piped and with a level control for fully automatic stock holding. With sterile overflow and sterile vent filter.

Nominal volume	80 Litre
Material	PE black



Booster pump

Fully integrated, self-priming, compact booster pump with extremely low-noise permanent magnet motor and water cooling. The integrated speed control enabling the keeping of the perfect pressure at the end users, meaning that the pump performance will increase with increasing demand. Delivered with built-in dry run protection.

Pumped liquid	Pure water
Rated flow	3 m ³ /h
Rated head	27 m
Connection size	R 1"



Optional components – EDI module

Low-energy, integrated EDI module for the final demineralization. Reliable high-purity water supply without regeneration or other interruptions. No chemicals needed. Lowest operating costs combined with high, constant quality. Regulating valves and flow meters for setting the pure water and concentrate flow.

Pure water quality	< 0.2 µS/cm typ. 0.055-0.1 µS/cm
Recovery rate	90-95 %



Optional components - Tabletop dispenser

- Ergonomic design for a one-handed operation
- All dosing functions can be easily executed with the rotary encoder at the dispensing handle
- The external dispenser can be placed independent of the production unit
- For an even greater range the handle can be detached and reattached with a simple hand movement
- Withdrawal reports ensure traceability of the withdrawn pure water
- GLP-compliant data storage via USB



Feed water requirements

Feed water quality	Softened or hardness stabilized potable tap water
Conductivity at 25°C	< 2000µS/cm
Total organic carbon (TOC)	< 1ppm
Inlet pressure*	1 – 6bar
Temperature	5 – 35°C

Additional pretreatment units are available if the feed water is out of specs

Pure water specifications

Performance at 10°C	40 l/h
Retention rate	> 99 % ions, germs and bacteria
Pure water quality (with EDI module)	< 0.2 µS/cm typ. 0.055-0.1 µS/cm

Technical data

Ambient temperature	+2 - 35°C
Supply voltage	200-240V / 50-60Hz
Connected load	670W
Connection size	Tube d8 inlet, R 1" outlet

Dimensions

